



Stronghold 30™

Heavy-Duty Safety Flooring

Features and Benefits

- Incorporates AltroSan™ Integrated Bacteriostat
- Incorporates Altro Easyclean™ Technology for low maintenance costs
- Superior slip resistance and durability
- Designed for heavy-use areas
- Excellent chemical resistance
- Low VOC emissions for improved air quality
- Does not contain DEHP or Phthalates

Applications

Stronghold 30 is suitable for commercial kitchens, industrial areas, chemical processing, mezzanine areas and heavy carts.

Specifications

Stronghold 30 is the natural choice for wet and greasy areas where safety cannot be compromised. It comes in 8 great color choices.

Product Specification	(All weights and measures are approximate)	
Thickness	0.12"	3.0mm
Roll Length	49'	15m
Width	6'7"	2m
Weight	6.3lbs/yd ²	3.4kg/m ²

Test Results

ASTM Standard	<i>(Tested in accordance with ASTM tests)</i>	
ASTM F 970	Static Load Limit	2000psi
ASTM D 2047	Slip Resistance	D.92
ASTM E 648	Critical Radiant Flux	Pass
ASTM E 662	Smoke Generation	Pass
ASTM F 1303/1700	Physical Properties	Pass
ASTM C 501	Taber Abrasion	Pass
ASTM D 1203	Volatile Loss	Pass
CAN/ULC-S102.2	Surface Burning	Pass

Sustainability

Category	LEED NC&CI Credits	Description Summary
Materials and Resources	4.1 & 4.2	Contains 10% Post-Consumer Recycled Content
Indoor Environmental Air Quality	EQ 4.3	Low VOC emitting materials
	EQ 4.1	Low VOC emitting materials



StrongholdData_RCM_11/09

