



Impressionist II™

Patterned Safety Flooring

Features and Benefits

- Incorporates Altro Easyclean™ Technology
- Incorporates AltroSan™ Integrated Technology
- Excellent slip resistance
- No finish required, just scrub with water and detergent
- Chip design helps hide soiling
- Colors specially selected to “Mix and Match”
- Does not contain DEHP or phthalates

Applications

Impressionist II is ideal for waiting rooms, procedure rooms, operating rooms, classrooms, corridors, restaurants, cafés and retail stores.

Specifications

Impressionist II is available in 12 attractive colors, you can “mix and match” to achieve a unique and stylish look.

Product Specification	(All weights and measures are approximate)	
Thickness	0.08”	2.0mm
Roll Length	66’	20m
Width	6’7”	2m
Weight	4.6lbs/yd ²	2.5kg/m ²

Test Results

ASTM Standard	(Tested in accordance with ASTM tests)	
ASTM F 970	Static Load Limit	500 psi
ASTM D 2047	Slip Resistance	W .70
ASTM E 648	Critical Radiant Flux	Pass
ASTM E 662	Smoke Generation	Pass
ASTM F 1303/1700	Physical Properties	Pass
ASTM C 501	Taber Abrasion	Pass
ASTM D 1203	Volatile Loss	Pass
CAN/ULC-S102.2	Surface Burning	Pass

Sustainability

Category	LEED NC&CI Credits	Description Summary
Materials and Resources	4.1 & 4.2	Contains 20% 10% Post-Consumer 10% Pre-Consumer Recycled Content
Indoor Environmental Air Quality	EQ 4.3	Low VOC emitting materials
	EQ 4.1	Low VOC emitting materials



ImpressionistData_RCM_11/09

