



Quartz Tile™

High Performance Tile Flooring

Features and Benefits

- PUR coating - polyurethane surface treatment for excellent cleaning
- Excellent durability and wear resistance
- Does not crack or break under impact or pressure, withstands 3500 psi
- Meets OSHA slip resistance guidelines for level surfaces

Applications

Quartz Tile is ideal for heavy pedestrian traffic, elevators, sales floors, cafeterias, classrooms, utility and storage areas, factory floors, and areas requiring the use of forklift trucks, pallet trucks and other wheeled traffic.

Specifications

Quartz Tile is available in 35 contemporary colors.

Product Specification	(All weights and measures are approximate)	
Thickness	0.10"	2.5mm
Size of Tiles	24" x 24"	610mm x 610mm
Area per Box	40 sq. ft.	3.72m ²
Weight per Box	41.4lbs.	18.8kg/m ²
Number of Tiles per Box	10 tiles	



Test Results

ASTM Standard	(Tested in accordance with ASTM tests)	
ASTM F 970	Static Load Limit	3500psi
ASTM D 2047	Slip Resistance	D .75
ASTM E 648	Critical Radiant Flux	Pass
ASTM E 662	Smoke Generation	Pass
ASTM F 1303/1700	Physical Properties	Pass
ASTM C 501	Taber Abrasion	Pass
ASTM D 1203	Volatile Loss	Pass
CAN/ULC-S102.2	Surface Burning	Pass

Sustainability

Category	LEED NC&CI Credits	Description Summary
Materials and Resources	4.1 & 4.2	Contains 30% Pre-Consumer Recycled Content
Indoor Environmental Air Quality	EQ 4.3	Low VOC emitting materials
	EQ 4.1	Low VOC emitting materials



QuartzData_RCM_11/09